

ASUS ESC8000 G4 LGA 3647 (Socket P) Rack (4U) Black, Stainless steel

Brand : ASUS

Product code: 90SF00H1-M00080

Product name : ESC8000 G4

- Powered by Intel® Xeon® Scalable Platform
 - High-density GPU server with hybrid computing power
 - ASUS-patented Adaptable Topology design
 - Scalable design for growing workloads
 - Comprehensive IT Infrastructure Management Solution
 - Efficient cooling with hot-swappable redundant fans and dedicated air tunnels
 - Exclusive thermal radar technology for energy efficiency
 - Simplified maintenance and management
 - Supports 100Gbps Intel® Dual Embedded Omni-Path Architecture
- LGA 3647, 24 DIMM max 3072GB RDIMM, 4U, Aspeed AST2500



Processor		Network	
Built-in processor *	✗	LAN controller	Intel® I350-AM2
Processor socket *	LGA 3647 (Socket P)	Ports & interfaces	
Number of processors supported *	2	USB 2.0 ports quantity *	2
Compatible processor series	Intel® Xeon®	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
Memory		Ethernet LAN (RJ-45) ports *	2
Number of DIMM slots *	24	VGA (D-Sub) ports quantity	1
Supported memory types *	DDR4-SDRAM	COM ports quantity	1
Supported DIMM module capacities	8GB, 16GB, 32GB, 64GB, 128MB	Logistics data	
Maximum internal memory	3 TB	Harmonized System (HS) code	84714100
Supported RDIMM clock speeds	2133,2400,2666 MHz	Design	
Storage		Chassis type *	Rack (4U)
Number of storage drives supported *	10	Product colour	Black, Stainless steel
Hot-swap HDD bays *	✓	Certification	BSMI, CE, FCC(Class A)
Supported storage drive interfaces	M.2, Serial ATA III	Power	
RAID levels	0, 1, 5, 10	Power supply *	1600 W
Graphics		AC input voltage	100 - 240 V
On-board graphics card model	Aspeed AST2500	AC input frequency	47 - 63 Hz
On-board graphics card memory	64 MB	80 PLUS certification	80 PLUS
Network		Operational conditions	
Ethernet LAN	✓	Operating temperature (T-T)	10 - 35 °C
Ethernet interface type	Fast Ethernet, Gigabit Ethernet	Storage temperature (T-T)	-40 - 70 °C
Ethernet LAN data rates	10,100,1000 Mbit/s	Storage relative humidity (H-H)	20 - 90%
Weight & dimensions			
		Width	439 mm
		Depth	798 mm
		Height	175.6 mm



4712900954005



0889349997345



889349997345

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.