

ASUS P11C-C/4L Intel C242 LGA 1151 (Socket H4) ATX

Brand : ASUS

Product code: 90SB06M0-M0UAY0

Product name : P11C-C/4L



- Powered by the Intel Xeon E platform
- 95W CPU and up to 64GB memory support (4 DIMMs)
- Rack-optimized design maximizes cooling for excellent thermal efficiency
- Flexible expandability with 6 SATA HDDs, 2 PCIe Gen3 slots and 1 PCI legacy slot
- Quad Intel I210AT Gigabit Ethernet with teaming support
- Dual M.2 for up to 32Gbps performance and data redundancy
- High-speed mini-SAS HD connections
- TPM-M 2.0 support for enhanced platform integrity
- Complete server management with ASUS Control Center
- Optional ASMB9-iKVM module available for 24/7 remote monitoring and diagnostics

ATX, LGA1151, Intel C242, 4x DDR4 2400/2666, PCI-E x8/x16, 6x SATA3, 4x Intel I210AT, Aspeed AST2500 32MB, USB 3.1, VGA

Processor		Rear panel I/O ports	
Processor manufacturer *	Intel	USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *	2
Processor socket *	LGA 1151 (Socket H4)	Ethernet LAN (RJ-45) ports *	4
Compatible processor series *	Intel® Celeron®, Intel® Core™ i3, Intel® Pentium®, Intel® Xeon®	VGA (D-Sub) ports quantity *	1
Memory		Network	
Supported memory types *	DDR4-SDRAM	Ethernet LAN	✓
Number of memory slots *	4	LAN controller	Intel® I210-AT
Memory slots type	DIMM	Features	
Memory channels	Dual-channel	Motherboard chipset *	Intel C242
ECC compatibility	ECC & Non-ECC	Component for *	PC
Supported memory clock speeds	2400,2666 MHz	Motherboard form factor *	ATX
Maximum internal memory *	64 GB	Motherboard chipset family *	Intel
Storage controllers		Expansion slots	
RAID levels	0, 1, 5, 10	PCI Express x8 slots	1
Graphics		PCI Express x16 slots	1
Graphics card	AST2500	PCI slots	1
Internal I/O		Number of M.2 (M) slots	2
USB 2.0 connectors *	1	Operational conditions	
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	1	Storage temperature (T-T)	10 - 35 °C
Number of SATA III connectors *	6	Operating temperature (T-T)	-40 - 70 °C
ATX Power connector (24-pin)	✓	Operating relative humidity (H-H)	20 - 90%
Number of chassis fan connectors	6	Logistics data	
EPS power connector (8-pin)	✓	Harmonized System (HS) code	84733020
TPM connector	✓	Packaging data	
Rear panel I/O ports		Package weight	1.3 kg
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	2	Weight & dimensions	
		Width	305 mm
		Depth	244 mm
		Other features	
		Weight	760 g



4718017055420



0192876055427



192876055427

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.