APC BGM1500B uninterruptible power supply (UPS) Line-Interactive 1.5 kVA 900 W





Brand : APC

Product code: BGM1500B

Product name : BGM1500B

- Resettable circuit breaker
- Simple battery replacement
- Intelligent battery management
- Green mode
- Customizable voltage-transfer points
- Customizable voltage sensitivity
- Transformer-block spaced outlets
- Boost and Trim Automatic Voltage Regulation (AVR)
- Cold-start capable
- Automatic self-test
- Battery failure notification
- LCD Status Display
- USB connection
- Audible alarms
- Disconnected battery notification
- Battery-protected and surge-only outlets
- Boost Automatic Voltage Regulation (AVR)
- Dataline surge protection
- Battery and surge protected outlets
- Surge only outlets

1500VA, Gaming Back-UPS, Pure Sinewave, 3 USB Charging Ports
APC BGM1500B. UPS topology: Line-Interactive, Output power capacity: 1.5 kVA, Output power: 900 W. AC outlet types: NEMA 5-15R, Power plug: NEMA 5-15P, Serial interface type: RJ-45. Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 257 Ah, Battery recharge time: 5 h. Product colour: Black, Cable length: 1.8 m, Display type: LCD. Cables included: Coaxial, USB cable

Features	
UPS topology *	Line-Interactive
Output power capacity *	1.5 kVA
Output power *	900 W
Waveform *	Sine
Input operation voltage (min) *	88 V
Input operation voltage (max) *	120 V
Input frequency *	60 Hz
Output operation voltage (min)	120 V
Output operation voltage (max)	120 V
Output frequency	60 Hz
Automatic Voltage Regulation (AVR)	✔
Maximum current	12 A
Surge energy rating	1080 J
Response time	8 ms
EMI/RFI noise filtering	✔
Noise level	45 dB
Surge protection	✔
Audible alarm(s)	✔
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm

Ports & interfaces	
AC outlet types	NEMA 5-15R
Power plug	NEMA 5-15P
USB port	✔
Serial interface type	RJ-45
Cabling technology	10/100/1000Base-T(X)

Battery	
Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	257 Ah
Number of batteries supported	1
Battery recharge time	5 h
Automatic battery test	✔
Cold start	✔

Design	
Cable length	1.8 m
Product colour *	Black
Display type	LCD

Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 40 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3048 m
Non-operating altitude	0 - 3048 m

Packaging content	
Cables included	Coaxial, USB cable
Manual	✔

Weight & dimensions	
Width	105 mm
Depth	408 mm
Height	291 mm
Weight	1.15 kg

Ports & interfaces	
Emergency Power Off (EPO) connector	✔

Packaging data	
Package width	105 mm
Package depth	408 mm
Package height	291 mm
Package weight	11.5 kg

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 22-SEP-2026. Prints or copies of Information are only valid on the printed Publication date