D-Link

D-Link DMS-3130-30TS/E network switch Managed L3 10G Ethernet (100/1000/10000) Desktop/Wall-Mounting Black





Brand : D-Link

Product code: DMS-3130-30TS/E

Product name : DMS-3130-30TS/E

- Multi-Gigabit 2.5G/5G/10G/25G support
- 2.5GBASE-T PoE+ and 5GBASE-T 60W PoE support
- x4 25G SFP28 uplink ports
- 6 kV surge protection on 2.5G/5G ports
- Up to 400Gbps of switching capacity
- Physically stacking of up to 9 units
- Integrated software image with powerful L2 and L3 features
- Power over Ethernet (PoE) options, up to 740W with RPS
- QoS and D-Link Safeguard Engine

Layer 3 Stackable Multi-Gigabit Managed Switches, UK

D-Link DMS-3130-30TS/E. Switch type: Managed, Switch layer: L3. Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000), Basic switching RJ-45 Ethernet ports quantity: 2, USB 2.0 ports quantity: 1, Console port: RJ-45. MAC address table: 32768 entries, Switching capacity: 360 Gbit/s. Networking standards: IEEE 802.11ad, IEEE 802.1ag, IEEE 802.3ah, IEEE 802.1p, IEEE 802.11d, IEEE 802.1s, IEEE 802.1AX,.... Power connector: AC-in jack. Rack mounting, Form factor: Desktop/Wall-Mounting

Management features	
Switch type *	Managed
Switch layer	L3
Quality of Service (QoS) support	✔
Web-based management	✔
System event log	✔

Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity *	2
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)
10G Ethernet (copper) ports quantity	2
SFP module slots quantity	24
Console port	RJ-45
USB 2.0 ports quantity	1
Power connector	AC-in jack

Network	
Networking standards *	IEEE 802.11ad, IEEE 802.1ag, IEEE 802.3ah, IEEE 802.1p, IEEE 802.11d, IEEE 802.1s, IEEE 802.1AX, IEEE 802.3x, IEEE 802.1v, IEEE 802.1Q, IEEE 802.1w, IEEE 802.1x
10G support *	✔
Port mirroring	✔
Flow control support	✔
Link aggregation	✔
Broadcast storm control	✔
Spanning tree protocol	✔
Ethernet Ring Protection Switching (ERPS)	✔
Fast leave	✔
VLAN support	✔

Security	
Authentication	Guest VLAN
Authentication type	RADIUS, TACACS+
Queue scheduling algorithms	Weighted Round Robin (WRR), Weighted random early detection (WRED), Strict Priority Queue (SPQ)

Multicast features	
Multicast support	✔
MLD entries	64

Protocols	
GARP VLAN Registration Protocol (GVRP)	✔
Routing protocols	OSPFv2, RIPng, OSPFv3, RIP-1, RIP-2

Design	
Rack mounting *	✔
Stackable *	✔
Form factor	Desktop/Wall-Mounting
Product colour	Black
Housing material	Metal
Number of fans	3 fan(s)
Safety	CB, cUL, BSMI, CCC

Performance	
Physical stacking (units)	9
Virtual stacking (units)	32
Noise level	52.5 dB
sFlow	✔
Mean time between failures (MTBF)	270340 h

Power	
Power source *	AC
Power supply included *	✔
Redundant power supply (RPS) support	✔
AC input voltage	100 - 240 V

Network	
Virtual LAN features	Protocol-based VLAN, MAC address-based VLAN, Port-based VLAN, Voice VLAN, Multicast VLAN, Private VLAN
Number of VLANs	4000

Data transmission	
Switching capacity *	360 Gbit/s
Forwarding rate	268 Mpps
MAC address table *	32768 entries
Number of queues	8
Jumbo frames support	✔
Jumbo frames	9000
Packet buffer memory	4 MB

Security	
DHCP features	DHCP client, DHCP relay, DHCP server, DHCP snooping
Access Control List (ACL)	✔
Access Control List (ACL) egress	512
Access Control List (ACL) ingress	2048
IGMP snooping	✔
IGMP entries	1024
Static port security	✔
SSH/SSL support	✔
Loop protection	✔
BPDU filtering/protection	✔

Power	
Power consumption (max)	74.26 W
Surge protection	✔
Surge protection voltage	6 kV

Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✘

Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%
Heat dissipation	253.38 BTU/h

Weight & dimensions	
Width	440 mm
Depth	250 mm
Height	250 mm
Weight	3.63 kg

Certificates	
Certification	FCC Class A, CE Class A, VCCI Class A, IC, RCM, BSMI, CCC



0790069467554



790069467554

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 21-SEP-2026. Prints or copies of Information are only valid on the printed Publication date